

ARIES IS

SINGLE-JET METER

DIEHL
Metering



APPLICATION

ARIES IS is a single jet water meter specifically designed for submetering market. It is characterised by its accurate metering capability, its ruggedness and versatility.

Its integrated radio module enables remote reading of the index and alarms of the meter in mobile mode (walk-by) or fixed network.

Developed within the framework of the MID, ARIES IS complies with the European regulations and holds sanitary conformity certificates.

FEATURES

- ▶ DN 15
- ▶ Q3=2.5 m³/h
- ▶ MID approval up to R=125H and R=63V
- ▶ Starting flow rate: 6 l/h
- ▶ Brass body
- ▶ Cold and hot water
- ▶ IZAR integrated 868 MHz and 434 MHz radio, PRIOS protocol
- ▶ Battery lifetime up to 10 years
- ▶ IP54: not suitable for wet environment

ARIES IS

SINGLE-JET METER

METROLOGICAL DATA

Nominal diameter	DN	mm	15	15
Length	L	mm	80	110
Nominal flowrate	Q ₃	m ³ /h	2.5	2.5
Body			brass	brass
R standard*	Q ₃ /Q ₁		80H-40V	125H-63V
Starting flowrate horizontal		l/h	12	6
Minimum flowrate horizontal	Q ₁	l/h	31	20
Transition flowrate horizontal	Q ₂	l/h	50	32
Minimum flowrate vertical	Q ₁	l/h	61.5	39.7
Transition flowrate vertical	Q ₂	l/h	100	63.5
Maximum flowrate	Q ₄	m ³ /h	3.125	3.125
Head loss at Q ₃		bar	0.56	0.59
Head loss at Q ₄		bar	0.88	0.93
Kvs (deltaP=Q ² /Kvs ²)			3.34	3.25

* other values on request - H=horizontal installation position / V=vertical installation position

APPROVAL

	ARIES IS
MID approval	LNE-30014 B2 type
Sanitary conformity	ACS WRAS PZH
Standards	ISO 4064 EN 14154 OIML R49

REACH

Information pursuant to Article 33 (1) of Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006:

This product series contains articles with the following substances in a concentration of more than 0.1% weight by weight (w/w):

- Lead (CAS no.: 7439-92-1)

TEMPERATURE AND PRESSURE

		ARIES IS
Water temperature	°C	+0.1 ... +50 +0.1 ... +90
Operating ambient temperature	°C	+1 ... +55
Storage temperature	°C	-10 ... +55
Nominal pressure	bar	16
Degree of protection		IP 54

TECHNICAL DATA IZAR INTEGRATED RADIO

		ARIES IS
Communication protocol		PRIOS
Frequency	MHz	868.95 (R3 mode) and 434.47 (R3 mode)**
Sending interval		Every 32 seconds
Standards		EN 300 220, CE, RED directive, EN 13757-3/-4
Transmission power	mW	16
Transmission mode		Unidirectional
Radio range		Up to 500 m depending on the environment
Power supply		3 V lithium battery
Typical battery lifetime		Up to 10 years*
Integrated functions		Current index Historical index value Remaining battery lifetime
Alarms management		Leak detection Meter stopped Overflow Underflow Backflow

*Under standard conditions of use and temperature. Theoretical lifetime, not guaranteed.


**434 MHz available for DN15/110 Q3=2.5. Other variants on demand.

Diehl Metering S.A.S. - Head Office - 67 rue du Rhône - BP 10160 - FR-68304 Saint-Louis Cedex - Phone: + 33 (0)3 89 69 54 00 - Fax: + 33 (0)3 89 69 72 20 - metering-France-info@diehl.com - www.diehl.com/metering
International Sales - 67 rue du Rhône - BP 10160 - FR-68304 Saint-Louis Cedex - Phone: + 33 (0)3 89 69 54 21 - Fax: + 33 (0)3 89 69 54 22 - metering-France-export@diehl.com
Subject to technical adjustments.

ARIES IS


SINGLE-JET METER

DIMENSIONS



Nominal diameter	DN	mm	15	15
Length	L	mm	80	110
Nominal flowrate	Q ₃	m ³ /h	2.5	2.5
Body			brass	brass
Width		mm	77	77
Height		mm	97	97
Thread connections	G	inch	3/4"	3/4"
Weight		kg	0.37	0.45

PRECISION CURVE



DN15 brass - Q3=2.5 R=125H

This technology doesn't require straight length.

OPTIONS

- Tamper-proof ring
- Non-return valve that entirely fits into the body