

# IZAR IOT GATEWAY COMPACT

RADIO | RECEIVER

**DIEHL**  
Metering



## APPLICATION

Diehl Metering empowers utilities and other industries with the most robust and efficient IoT connectivity solution on the market for maximum accessibility. With the IZAR IoT GATEWAY Compact, the reception of radio data coming from IoT sensors for smart city as well as smart metering applications is possible with only one device, as mioty® and mioty® for Metering as well as wM-Bus receivers are included and LoRa® technology is pre-installed. Discover the power of Diehl Metering with the IZAR IoT GATEWAY Compact!

## FEATURES

- ▶ All-in-one multi-technology receiver for Smart Metering and Smart City LPWAN infrastructure
- ▶ Effective data protection and communication security
- ▶ Highest data timeliness (live streaming possible)
- ▶ Capacity for up to 50,000 devices
- ▶ Intelligent telegram filtering
- ▶ Ethernet 10/100
- ▶ LTE
- ▶ 868 MHz
- ▶ mioty®, mioty® for Metering, wireless M-Bus T1 & C1 and LoRa®

# IZAR IOT GATEWAY COMPACT

RADIO | RECEIVER

## PRINCIPLE OF OPERATION

The IZAR IoT GATEWAY Compact offers a way to handle radio telegrams from different LPWAN standards in a data encoding agnostic way. All telegrams are collected, filtered, processed and exported fully automatically, dynamically and securely to the selected head-end system.

## GENERAL

IZAR IoT GATEWAY Compact	
Capacity	Up to 50,000 devices
Antenna	3 SMA connections (for mioty® and mioty® for Metering, wireless M-Bus and LoRa®)
Data granularity	Individually adjustable: "Stream mode" (no data reduction) or "Batch mode" (with export after aggregation every 1 minute - 24 hours)
Range of reception	Up to 11 km outdoors, depending on type of connectivity, antenna and location.

## TECHNICAL DATA

IZAR IoT GATEWAY Compact	
Version	868 MHz
Interfaces	Ethernet 10/100, LTE-FDD: B1/B3/B7/B8/B20/B28A, WCDMA: B1/B8, GSM/EDGE: B3/B8
External power supply	AC 100 ... 240 V, 1.5 A, 50-60 Hz
Power connector	DC 12.0 V, max. 5.0 A
Typical power consumption	9 W
Supported LPWAN	Mioty® band EU1, mioty® for Metering, wM-Bus mode T1 & C1 and LoRa® (8 channels)

## AMBIENT CONDITIONS

IZAR IoT GATEWAY Compact	
Operating temperature	°C -20 ... +55
Storage temperature	°C -20 ... +70
Protection class	IP 20 (indoor)
Humidity	% 10 ... 85 (non-condensing)

## DIMENSIONS

IZAR IoT GATEWAY Compact	
Length	mm 241
Width	mm 121
Height	mm 70
Weight	kg 0.78