

IZAR OH BT 2

Radio | Bluetooth Optohead

DIEHL
Metering



APPLICATION

The opto head is used for readout and configuration of Diehl Metering meters and system components by optical interface. The data is transmitted via Bluetooth® to mobile or desktop computers.

FEATURES

- ▶ Combined IrDa and ZVEI interface
- ▶ Typical operating time: up to 14 h continuous duty
- ▶ Typical charging time: 3.5 h
- ▶ On/Off slide switch
- ▶ Status LEDs for: battery state, Bluetooth® link and data transmission
- ▶ USB battery charging unit
- ▶ Metal ring for carrying strap

IZAR OH BT 2

Radio | Bluetooth Optohead


TECHNICAL DATA

IZAR OH BT 2		
Power supply		Litium ion battery 3.7 V / 900 mAh; charging unit input 230 V, output USB 5 V / 700 mA
Bluetooth® specification		2.4 GHz, version 2.1, class 2
Bluetooth® range		Up to 10 m
Transmission frequency		2.4 GHz
Data transmission rate		2.1 Mbit/s
Optical modes		ZVEI, IrDa
Weight	g	55

AMBIENT CONDITIONS

IZAR OH BT 2		
Operating temperature	°C	0 ... 40
Protection class	IP	40

DIMENSIONS



IZAR OH BT 2		
Width	B	mm 64
Diameter	H	mm 32.5